Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

*
1 Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: SIKACERAM 235 FLEX**
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Construction products.
· **Application of the substance / the mixture** Construction applications.

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Gilar LTD - Sika Israel
Hamatechet st. 6, 60920 Qadima , Israel
Phone: +972 98994006, Mobile:+972 544527212 , Fax: +972 98994016.

· **Further information obtainable from:** Product safety department.
· **1.4 Emergency telephone number:** +972 (0) 8994004 9

*
2 Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms** GHS07
· **Signal word** Warning

· **Hazard-determining components of labelling:**
Cement, White Cement , EN 197-1 CEM 1
· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
· **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.

(Contd. on page 2)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 1)

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.

· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

*
3 Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**		
14808-60-7	Quartz (SiO2) substance with a Community workplace exposure limit	>50%
	Cement, White Cement , EN 197-1 CEM 1 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	>30%
544-17-2	calcium diformate Eye Irrit. 2, H319	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

*
4 First aid measures

· **4.1 Description of first aid measures**
· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*
5 Firefighting measures

· **5.1 Extinguishing media**
· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **5.2 Special hazards arising from the substance or mixture**
Carbon monoxide , carbon dioxide, hydrogen chloride gases.
At low oxygen level: acetic acid.

(Contd. on page 3)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 2)

· **5.3 Advice for firefighters**
· **Protective equipment:** Use respiratory protection independent of recirculated air.

*
6 Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid dust formation . Do not breathe dust.
· **6.2 Environmental precautions:**
Cover any spilled material in accordance with regulations to prevent dispersal by wind.
· **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
7 Handling and storage

· **7.1 Precautions for safe handling**
Avoid dust formation.
Take precautionary measures against electrostatic charging.
Keep away from open flames, heat and sparks.
Prevent moisture.
· **Information about fire - and explosion protection:** No special measures required.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe precutionary measures against dust explosion.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:**
Keep container tightly sealed.
Keep in a dry and cool place.
· **7.3 Specific end use(s)** No further relevant information available.

*
8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
14808-60-7 Quartz (SiO2)	
TLV	Long-term value: 0,1 mg/m³ respirable fraction

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 3)

· **8.2 Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
· **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **Eye protection:**



Tightly sealed goggles

*
9 Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Powder
Colour:	According to specification.
· **Odour:**	Odourless
· **Odour threshold:**	Not determined.
· **pH-value:**	Not applicable.

(Contd. on page 5)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 4)

· **Change in condition**	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· **Flash point:**	Not applicable.
· **Flammability (solid, gaseous):**	Not determined.
· **Ignition temperature:**	
Decomposition temperature:	Not determined.
· **Self-igniting:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined.
Upper:	Not determined.
· **Vapour pressure:**	Not applicable.
· **Density:**	Not determined.
· **Relative density**	Not determined.
· **Vapour density**	Not applicable.
· **Evaporation rate**	Not applicable.
· **Solubility in / Miscibility with water:**	Insoluble.
· **Partition coefficient (n-octanol/water):**	Not determined.
· **Viscosity:**	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· **Solvent content:**	
Organic solvents:	0,0 %
VOC (EC)	0,00 %
Solids content:	100,0 %
· **9.2 Other information**	No further relevant information available.

*
10 Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability** Stable under recommended storage conditions.
· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** Heat, flames and sparks.
· **10.5 Incompatible materials:** Strong oxidizing agents, ammonium salts and aluminum metal.

(Contd. on page 6)

Safety data sheet
According to1907/2006\ EEC

(Contd. of page 5)

· **10.6 Hazardous decomposition products:**
Carbon monoxide, carbon dioxide.
At increased temperature: acetic acid.

*
11 Toxicological information

· **11.1 Information on toxicological effects**
· **Acute toxicity** Based on available data, the classification criteria are not met.
· **Primary irritant effect:**
· **Skin corrosion/irritation**
Causes skin irritation.
· **Serious eye damage/irritation**
Causes serious eye irritation.
· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
· **Carcinogenicity** Based on available data, the classification criteria are not met.
· **Reproductive toxicity** Based on available data, the classification criteria are not met.
· **STOT-single exposure**
May cause respiratory irritation.
· **STOT-repeated exposure** Based on available data, the classification criteria are not met.
· **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:** Generally not hazardous for water
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **12.6 Other adverse effects** No further relevant information available.

*
13 Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 6)

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **14.1 UN-Number** · **ADR, ADN, IMDG, IATA**	Void
· **14.2 UN proper shipping name** · **ADR, ADN, IMDG, IATA**	Void
· **14.3 Transport hazard class(es)** · **ADR, ADN, IMDG, IATA** · **Class**	Void
· **14.4 Packing group** · **ADR, IMDG, IATA**	Void
· **14.5 Environmental hazards:**	Not applicable.
· **14.6 Special precautions for user**	Not applicable.
· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **UN "Model Regulation":**	Void

*
15 Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
· **Hazard pictograms** GHS07
· **Signal word** Warning

· **Hazard-determining components of labelling:**
Cement, White Cement , EN 197-1 CEM 1
· **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
· **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves.

(Contd. on page 8)

Safety data sheet
According to1907/2006\ EEC

Printing date 15.01.2017 **Version number 1** **Revision: 15.01.2017**

Trade name: SIKACERAM 235 FLEX

(Contd. of page 7)

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*
16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
All information contained in the present sheet is based on the manufacturer data.The use of this product is not subject to our direct control : therfore , users must under their own responsibility comply with the current health and safety laws and regulation.

· **Relevant phrases**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

· **Department issuing SDS:** Product safety department.
· **Contact:**
Gilar LTD - Sika Israel
Hamatechet st. 6, 60920 Qadima , Israel
Phone: +972 98994006, Mobile:+972 544527212 , Fax: +972 98994016.
· **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**