Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance/preparation

Product name or Trade name :

Sikafloor-410

Use of the substance/preparation : Chemical product for construction and industry

Company/undertaking identification

Manufacturer/Distributor	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ United Kingdom
Telephone no.	:	01707 394444
Fax no.	:	01707 329129
e-mail address of person responsible for this SDS	:	EHS@uk.sika.com
Emergency telephone number	:	+44 (0)1707 363899 (available during office hours).

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10
Xn; R20/21
Xi; R38
R43
R52/53

Physical/chemical hazards : Flammable.

Human health hazards : Harmful by inhalation and in contact with skin. Irritating to skin. May cause sensitisation by skin contact.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer.

See section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical family/ Characteristics : Polyisocyanate, containing solvent

Ingredient name	CAS number	%	EC number	Classification	
xylene	1330-20-7	20-25	215-535-7	R10 Xn; R20/21 Xi; R38	[1] [2]
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	10-15	265-185-4	R10 Xn; R65 R66, R67 N; R51/53	[1]
Hexamethylene-1,6-diisocyanate Homopolymer	28182-81-2	2.5-25		R43 R52/53	[1]
ethylbenzene	100-41-4	2.5-10	202-849-4	F; R11 Xn; R20	[1] [2]
2-methoxy-1-methylethyl acetate	108-65-6	1-5	203-603-9	R10	[2]

3. COMPOSITION/INFORMATION ON INGREDIENTS

solvent naphtha (petroleum), light arom.	64742-95-6	<0.25	265-199-0	R10 Xn; R65 Xi; R37 R66, R67 N; R51/53	[1]
Dibutyltin dilaurate	77-58-7	0.1-0.25	201-039-8	Muta. Cat. 3; R68 Repr. Cat. 2; R60, R61 T; R48/25 Xn; R22 Xi; R38 N; R50/53	[1] [2]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

Inhalation : Get medical attention.

Ingestion : Do not induce vomiting unless directed to do so by medical personnel. Maintain an open airway. Seek immediate medical attention.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Use dry chemical, CO_2, water spray (fog) or foam.

Not suitable : Do not use water jet.

Special exposure hazards : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment (see section 8). Evacuate surrounding areas.

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.

Small spill : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE

Handling : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.

Storage : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended : Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name	Occupational exposure limits
xylene	**EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.** STEL: 441 mg/m³ 15 minute(s). STEL: 100 ppm 15 minute(s). TWA: 220 mg/m³ 8 hour(s). TWA: 50 ppm 8 hour(s).
Hexamethylene-1,6-diisocyanate Homopolymer	**EH40/2005 WELs (United Kingdom (UK), 8/2007). Skin sensitiser.** STEL: 0.07 mg/m³, (as NCO) 15 minute(s). TWA: 0.02 mg/m³, (as NCO) 8 hour(s).
ethylbenzene	**EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.** STEL: 552 mg/m³ 15 minute(s).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	STEL: 125 ppm 15 minute(s). TWA: 100 ppm 8 hour(s). TWA: 441 mg/m³ 8 hour(s).
2-methoxy-1-methylethyl acetate	**EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.** STEL: 548 mg/m³ 15 minute(s). STEL: 100 ppm 15 minute(s). TWA: 274 mg/m³ 8 hour(s). TWA: 50 ppm 8 hour(s).
Dibutyltin dilaurate	**EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin. Notes: as Sn** STEL: 0.2 mg/m³, (as Sn) 15 minute(s). TWA: 0.1 mg/m³, (as Sn) 8 hour(s).

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapour filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.

Eye protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Form : Liquid.

Colour : Various.

Odour : Hydrocarbon.

Important health, safety and environmental information

Flash point : Closed cup: ~33°C (91.4°F)

9. PHYSICAL AND CHEMICAL PROPERTIES

Explosion limits : Lowest known value:
Lower: 0.6% (Naphtha (petroleum), hydrodesulfurized heavy)
Highest known value:
Upper: 7% (xylene,ethylbenzene)

Vapour pressure : Highest known value: 0.8 kPa (6 mm Hg) (xylene,ethylbenzene)

Density : ~0.95 g/cm^3 [20°C (68°F)]

Solubility : Insoluble in the following materials: water

10. STABILITY AND REACTIVITY

Stability : The product is stable.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Materials to avoid : Reactive or incompatible with the following materials:
oxidizing materials

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : Harmful by inhalation. May cause irritation.

Ingestion : Irritating to mouth, throat and stomach.

Skin contact : Harmful in contact with skin. Irritating to skin. May cause sensitisation by skin contact.

Eye contact : May cause eye irritation.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

12. ECOLOGICAL INFORMATION

Environmental effects : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Water polluting material. May be harmful to the environment if released in large quantities.

13. DISPOSAL CONSIDERATIONS

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European waste catalogue (EWC) : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Packaging : Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

13. DISPOSAL CONSIDERATIONS

15 01 10* packaging containing residues of or contaminated by dangerous substances

14. TRANSPORT INFORMATION

International transport regulations

ADR

UN number	:	UN1263
ADR Class	:	3
Classification code	:	F1
Packing group	:	III
Proper shipping name	:	Paint
Label No.	:	3

IMDG

UN number	:	UN1263
IMDG Class	:	3
Packing group	:	III
Proper shipping name	:	Paint
Emergency schedules (EmS)	:	F-E, S-E
Marine pollutant	:	No
Label no.	:	3

IATA

UN number	:	UN1263
IATA Class	:	3
Packing group	:	III
Proper shipping name	:	Paint
Label no.	:	3

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols	:	Xn Harmful
Contains	:	xylene Hexamethylene-1,6-diisocyanate Homopolymer
Risk phrases	:	R10- Flammable. R20/21- Harmful by inhalation and in contact with skin. R38- Irritating to skin. R43- May cause sensitisation by skin contact. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	:	S36/37- Wear suitable protective clothing and gloves.
Additional warning phrases	:	Contains isocyanates. See information supplied by the manufacturer.
VOC content (EU)	:	VOC (w/w): 49.33%

National regulations

15. REGULATORY INFORMATION

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP 4)
Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as amended)
Health & Safety at Work Act 1974
Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR)
The Environmental Protection (Duty of Care) Regulations 1991
Hazardous waste regulations 2005
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE
General Approved Code of Practice to COSHH Regulations, HSE.
EH40, Workplace Exposure Limits, HSE (as updated).
HS(G) 53, Respiratory Protection Equipment - a Practical Guide for Users, HSE.

16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and 3 : R11- Highly flammable.
R10- Flammable.
R68- Possible risk of irreversible effects.
R60- May impair fertility.
R61- May cause harm to the unborn child.
R48/25- Also toxic: danger of serious damage to health by prolonged exposure if swallowed.
R20- Also harmful by inhalation.
R22- Also harmful if swallowed.
R20/21- Also harmful by inhalation and in contact with skin.
R65- Also harmful: may cause lung damage if swallowed.
R37- Irritating to respiratory system.
R38- Irritating to skin.
R43- May cause sensitisation by skin contact.
R66- Repeated exposure may cause skin dryness or cracking.
R67- Vapours may cause drowsiness and dizziness.
R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications referred to in sections 2 and 3 : F - Highly flammable
Muta. Cat. 3 - Mutagen category 3
Repr. Cat. 2 - Toxic to reproduction category 2
T - Toxic
Xn - Harmful
Xi - Irritant
N - Dangerous for the environment

History

Date of printing : **13.09.2020.**

Date of issue : **13.09.2020.**

Date of previous issue : **16.03.2020.**

Indicates information that has changed from previously issued version.

Notice to reader

16. OTHER INFORMATION

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.