



סדרת גופי תאורה שקועי תקרה מתכוננים, בעיצוב עדין בשלושה גדלים 3W/7W/12W. בהספק 7W - שיטה ייחודית לבחירת גוון אור על ידי לחיצת כפתור. חסכוני בצריכת חשמל וקל להתקנה. מתאים להנמכת גבס סטנדרטית, לשימוש במסדרונות, חדרי מגורים, מבואות ועוד.

מק"ט - 72112296

TD30-7W 38° + CABLE WHITE 3CCT - דגם

קישור לדף מוצר ואביזרים נלווים באתר




1 Year
Guarantee

220-240V
50-60Hz



IP20

מתאים לדרשות
התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Height	38mm
Diameter	90mm
Product weight	70g
Cut hole	75mm

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	PC
Cover finishing	Clear
Cover material	PC
Lens material	PC

ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	7W
Nominal current	0.05A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable driver mode	No

APPLICATION & MOUNTING

יישומים

Application environment	Indoor
Mounting type	Recessed
Mounting location	Ceiling
Type of protection	IP20
Ambient temperature range	0...+35°C

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	80Lm/W
Luminous flux	560Lm
CCT	3000/4000/6000K
CRI	>80
LED manufacturer	Hongli Zhihui
Chip type	SMD 2835
Beam angle	60°
CIE class	Direct
Efficiency	100%

CERTIFICATES & STANDARDS

תקנים

Nisko Class	ECO 1 Year
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-2
CE	IEC 60598-1 IEC 60598-2-2 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20

PERFORMANCE

ביצועים

Lifespan (Hr)	25000Hrs
---------------	----------