




סדרת גופי תאורת LED בדרגת אטימות IP44. שלושה גווני אור בגוף אחד - חם, ניטרלי או קר. עיצוב פונקציונאלי ומינימליסטי, כיסוי אופטי ייחודי למניעת סנוור, UGR<19, שימוש בדרייבר חיצוני ללא ריצוד. להארת מבואות, שטחים מסחריים, משרדים, מבנים ציבוריים, מסדרונות, מבואות ועוד.

מק"ט - 71170106

דגם - Q-22-30WR

קישור לדף מוצר ואביזרים נלווים באתר



3 YEAR GUARANTEE

VALUE


220-240V
50-60Hz

IP20

IP44

IK04

מחירים לרשימת מחירים | התקן הישראלי



DIMENSIONS & WEIGHT

מידות ומשקל

Height	35mm
Diameter	220mm
Product weight	739g
Cut hole diameter	205mm

MATERIALS & COLORS

מבנה וגימור

Product color	white
Body material	aluminum
Protection class IEC 62262	IK04
Cover finishing	Anti Glare Crystal
Cover material	PC



ELECTRICAL DATA

נתונים חשמליים

Nominal wattage	28W
Nominal current	0.13A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	External LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIF030YA(H)0700H
Driver output current	700mA
Dimmable driver mode	No
Power factor	>0.96
THDi	<20%
Output ripple current	≤0.5%
Inrush current	60A
Inrush current time T _{h50}	350µs
Max. no. of lum. On circuit break. B10 A	12
Max. no. of lum. On circuit break. B16 A	20
Max. no. of lum. On circuit break. C10 A	20
Max. no. of lum. On circuit break. C16 A	34
Optional driver ON/OFF	LF 17900107
Optional driver 1-10V	LF 17900218
Optional driver DALI	LF 17900252

APPLICATION & MOUNTING

יישומים

Application environment	Indoor
Mounting type	Recessed
Mounting location	Ceiling
Type of protection	IP20/IP44
Ambient temperature range	-20...+35°C

CERTIFICATES & STANDARDS

תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-2
CB	IEC 60598-1 IEC 60598-2-2 IEC 61347-1 IEC 61347-2-11 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20/IP44
Protection class IK 62262 (shock resistance)	IK04
ISO 9001	√

PERFORMANCE

ביצועים

Lifespan (Hr)	80000Hrs
---------------	----------



PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	100Lm/W
Luminous flux	2800(4K)Lm
CCT	2700/3000/4000K
CRI	>80
LED manufacturer	XuYu
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
UGR level	<19
Efficiency	100%